

NEW

AQUARIA 18 P

AQUARIA 18 P Code 01969




FEATURES

- Dehumidification capacity: 18 lt/24h
- Tank capacity: 5,5 lt
- Digital control panel
- LED display Ambient temperature and humidity visualization
- Manual humidistat (20%-90% R.H.)
- Auto mode: keeps relative humidity at optimal level (60% R.H.)
- Programmable on-off timer from 1 to 24h
- Sleep Function: lowest fan speed
- Turbo function: maximum fan speed
- Continuous draining mode
- Autoshut off with full tank
- Autorestart function
- Automatic defrost function
- Washable antidust filter
- Active carbon filter
- For rooms up to: 80 m³



INTEGRATED TIMER
Programmable on/off from 1 to 24 hours.



DIGITAL CONTROL PANEL
LED display and digital controls.




LAUNDRY MODE
For quick drying of laundry.



PRACTICAL
Thanks to the handle and the transportable wheels.



HUMIDITY AND TEMPERATURE CONTROL
Humidity level control and room temperature display.



PURE SYSTEM
Anti-dust filter and active carbon filter, for better air quality.

Available
from February

AQUARIA 18 P

	Code	01969
	EAN	8021183019698
Dehumidification capacity (2)	l/24h	18
Heating capacity	W	-
Power absorption in dehumidification mode (1)	W	210
Nominal absorption in dehumidification mode (1)	A	1.4
Max. power absorption in dehumidification mode (2)	W	240
Max. absorption in dehumidification mode (2)	A	1.5
Max. power absorption in dehumidification mode (U.L.U.)	W	270
Protection level		IP 20
Fan speeds		2
Tank capacity	l	5.5
Air volume (max)	m ³ /h	160
Dimensions (W x H x D with wheels)	mm	335 x 587 x 240
Packing dimensions (W x H x D)	mm	384 x 645 x 294
Noise level	dB(A)	≤45
Weight (without packing)	kg	15
Weight (with packing)	kg	16.5
Refrigerant gas	Type	R290
Global warming potential of refrigerant GWP	kg CO ₂ eq.	3
Global warming potential of refrigerant	Tonn. CO ₂ eq.	-
Refrigerant gas charge	kg	0.08
Minimum floor area for installation, use and storage	m ²	4,00
Plug		SCHUKO
Power supply	V-F-Hz	220-240 - 1 - 50
Power supply min - max	V	207- 254
Conformity Mark		CE
Protection level Mark		TUV SUD-GS
Air filter		✓
Carbon filter		✓
Continuous operation with hose		✓
Humidity level power settings		✓
Indoor humidity visualizer		✓
Indoor temperature visualizer		✓
Tank full light		✓
Timer (turn on and turn off)		✓
Laundry function		✓
Defrosting device		✓

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)